DECLARATION OF PERFORMANCE

Product name: Modulier® Design MatFlooring, modular aluminium-rail entrance matting system

Unique ID code of the product type: Modulier® | **Number:** Modulier-CTX-2026

Intended use: in entrances, exits, escape routes, and corridors

Manufacturer and distributor: Cleartex Kft. 2038 Sóskút, Bolyai János u. 10. Hungary
Contact: +36 (23) 887-400, cleartex@cleartex.hu

Aluminium rail alloy: AlMgSi (EN AW 6060 T66):

- Profile height: 13 mm (Modulier 17), 6,4 mm (Modulier 10)
- Total system height with inserts: 17 mm (Modulier 17), 10 mm (Modulier 10)

Declared performance based on supplier documentation:

- Mechanical resistance and load-bearing capacity according to the EN AW 6060 aluminium Declaration of Performance
- Extruded aluminium structural profile: EN AW 6060
  (Harmonised standard: EN 15088, AVCP system: level 2+)
- Fire classification: A1 (non-combustible), according to European standards (EN 13501-1)

Inserts used in the Modulier® system:

- Insert materials: **Classic:** 100% polyamid **Aktív:** ECONYL® **Welcome:** ECONYL®

Declared performance based on supplier documentation:

	Cleartex Classic	Cleartex Aktív	Cleartex Welcome
Surface thickness ISO 1765	9 mm	9 mm	9 mm
Fire resistance EN 13501-1	Bfl-s1, G, NCS	Bfl-s1, G, NCS	Bfl-s1, G, NCS
Slip resistance EN 13893	μ > 0.30	μ > 0.30	μ > 0.30

CPR compliance: The assessment and verification of constancy of performance of the system are carried out in accordance with the harmonised standards applicable to its components. The declared performances are determined based on the Declarations of Performance of the construction products covered by the CPR.
The Declarations of Performance and test reports of the components are available at the manufacturer.
The Modulier® system does not declare any performance that is not included in the Declarations of Performance of its components.

The performance of the above-identified product system conforms to the declared performances. The manufacturer assumes sole responsibility for issuing this Declaration of Performance.

Usage and maintenance information:
The Modulier® entrance matting system is suitable for pedestrian and wheelchair traffic (Modulier® 17 also for shopping trolley traffic). During use and maintenance, sharp or hard tools must be avoided as they may cause permanent damage. The product should be cleaned using dry or wet vacuuming and high-pressure water vacuuming.
The warranty is valid for 5 years, provided that the product is properly installed, regularly maintained, used as intended, and the warranty certificate is returned.

Issued in Sóskút, 01 December 2025

Cleartex Kft.
2038 Sóskút, Bolyai János u. 10.
Adószám: 10820201-2-13
Bank: 10400023-49554957-51561008

Ilona Katalin Huber
CEO